



Specifications Ledvance LED Panel Performance 33W 3100lm - 830 Warm White | 60x60cm - UGR <19 - Dali Dimmable

[View Product](#)

## General Information

|                          |                                 |
|--------------------------|---------------------------------|
| SKU                      | 236379                          |
| EAN                      | 4058075225435                   |
| Manufacturer Code        | 4058075225435                   |
| Brand                    | Ledvance                        |
| Manufacturer Name        | PL PFM DALI 600 33W/3000K UGR19 |
| Any Lamp all-in warranty | 5 Years                         |
| Average Lifetime (h)     | 80000                           |
| Series                   | Performance                     |

## Technical Information

|                             |                    |
|-----------------------------|--------------------|
| Technology                  | LED Integrated     |
| Replaces (Watt)             | 4x18               |
| Wattage                     | 33W                |
| Voltage (V)                 | 220-240            |
| Dimmable                    | Dimmable with Dali |
| Colour Code                 | 830 Warm White     |
| Colour temperature (Kelvin) | 3000 Warm White    |
| Colour Rendering (Ra)       | 80-89              |
| Colour of Light             | White              |
| Light colour options        | Single Color       |

|                          |                   |
|--------------------------|-------------------|
| Luminous Flux (Lumen)    | 3100lm            |
| Luminous Efficacy (lm/W) | 95                |
| IP-rating                | IP20              |
| Impact Protection (IK)   | IK03 - 0.35 joule |
| Fixture Connection       | Terminal, 3-pole  |
| Driver Included          | Yes               |
| Power factor             | >0.95             |
| Product Type Category    | LED Panel         |

## Fixture Information

|                       |                                |
|-----------------------|--------------------------------|
| Mounting Method       | Recessed                       |
| Unified Glare Rating  | < 19 - for offices and schools |
| Optical Cover         | PS (Polystyrene)               |
| Operating Temperature | -10 to +40                     |
| Emergency Lighting    | No Emergency Unit              |
| Colour of the Fixture | White                          |
| Housing               | Aluminium                      |
| Colour of material    | White                          |

## Dimensions

|                |         |
|----------------|---------|
| LED panel size | 60x60cm |
| Length (mm)    | 595     |
| Width (mm)     | 595     |
| Height (mm)    | 9       |

### Why Any-lamp?



Order from the **largest lighting specialist** in Europe



**Customised** quotation

### Sensor Information



Up to **7 years warranty**



**Easy** return process

|                |           |
|----------------|-----------|
| Type of sensor | No Sensor |
|----------------|-----------|