



Specifications Ledvance LED
 Downlight Comfort Opal Aluminium
 18W/15W/12W
 2160lm/1800lm/1440lm 95D - 930-940
 CCT | Cutout 200mm - IP44 - Best
 Colour Rendering - Dali Dimmable

[View Product](#)

General Information

| | |
|--------------------------|---|
| SKU | 255056 |
| EAN | 4099854491108 |
| Manufacturer Code | 4099854491108 |
| Brand | Ledvance |
| Manufacturer Name | DL CMFT DA D150 P 18W MS 940 U19 WTLEDV |
| Any Lamp all-in warranty | 5 Years |
| Average Lifetime (h) | 100000 |

Technical Information

| | |
|-----------------------------|--------------------|
| Emergency Lighting | No Emergency Unit |
| Tiltable | No |
| Technology | LED Integrated |
| Replaces (Watt) | 2x18 |
| Wattage | 18W |
| Voltage (V) | 220-240 |
| Dimmable | Dimmable with Dali |
| Colour Code | 930 Warm White |
| Colour temperature (Kelvin) | 3000 Warm White |
| Colour Rendering (Ra) | 90-99 |

| | |
|--------------------------|--------------------------------|
| Colour of Light | White |
| Light colour options | Single Color |
| Beam Angle (degree) | 55 |
| Luminous Flux (Lumen) | 2160lm |
| Luminous Efficacy (lm/W) | 120 |
| Power factor | >0.90 |
| Unified Glare Rating | < 19 - for offices and schools |
| Optical Cover | Opal |
| Product Type Category | LED Downlight |

Fixture Information

| | |
|------------------------|------------------------|
| Mounting Method | Recessed |
| Cut out (mm) | 150 |
| IP-rating | IP44 |
| Impact Protection (IK) | IK03 - 0.35 joule |
| Operating Temperature | -20 to +40 |
| Housing | Aluminium |
| Colour of the Fixture | White |
| Fixture Connection | PI [Push-in connector] |

Dimensions

| | |
|---------------|-----|
| Height (mm) | 92 |
| Diameter (mm) | 160 |

 **Sensor Information** Order from the **largest lighting specialist** in Europe  **Customised** quotation

Type of sensor  **Up to 7 years warranty**  **Easy return process**
No Sensor